

Kvalitet: **453**
Quality:

Kvalitet: **453**
Quality:

Tekniske Spesifikasjoner/Technical Characteristics

| | | |
|---|--------------------------|--|
| Vev <i>Base fabric</i> | | Polyester, 1100 dtex, 2-skaft |
| Belegg <i>Coating</i> | | PVC |
| Bredde <i>Width</i> | EN 1848-2 | 204 cm |
| Vekt <i>Weight</i> | EN 1849-2 | 700 g/m ² |
| Rivestyrke <i>Tear resistance</i> | EN 12310-2/ DIN 53356 | 400/300 N |
| Strekstyrke <i>Tensile strength</i> | EN 12311-2 | 3000/2900 N/5 cm |
| Adhesjon <i>Adhesion</i> | DIN 53357 | 100 N/5 cm |
| Flammemotstand <i>Flame retardancy</i> | SIS 650082 | Tilfredsstillende <i>Satisfactory</i> |
| Temperaturbestandighet <i>Temperature resistance</i> | EN 495-5/DIN 53361 | + 70 °C - 30 °C |

De oppgitte verdiene er gjennomsnittsverdier fra produksjonen. Vi forbeholder oss retten til endringer uten varsel.
Technical values are average values from the production. The information may change at any time without prior notice.

Eksempler på bruksområde: **Haller, flat-presenning, draperier**
Suitable applications: **Soft skin buildings, flat tarpaulins, industrial room dividers**

991 – Grå/Grey
 NSC kode/NCS code: 2000

664 – Blå/Blue
 NSC kode/NCS code: 3060-R90B

001 – Hvit/White

442 – Grønn/Green
 NCS kode/NCS code: 6020-B90G

118 Rød/Red
 NSC kode/NCS Code: 1080-Y90R

Kvalitet: **453**
Quality:



Godkjenninger:
Approvals:

| Produkt/Product: | Godkjent av/Approved by: |
|----------------------------------|--|
| Kvalitet: 453 Quality: | SINTEF Produktdokumentasjon Nr. Sintef EA-133 Documentation No. Sintef EA-133 SITAC Typgodkännande 2935/81 Swedish Technical Approval 2935/81 ETA Godkendelse MK 6.10/0573 Approval MK 6.10/0573 |

